

International Journal of Research in Management, Science and Technology

# Issue - 13, Vol-07, pp. 96-106, Jan-Jun 2017 CLEAR International Journal of Research in Management, Science and **Technology**

# **RESEARCH ARTICLE**

# AN ENHANCED SECURITY USING MULTIMODAL **BIOMETRIC AUTHENTICATION SYSTEM**

P Sivakumar. Dr. S. Senthamarai Kannan

1. Associate Professor Computer Science and Engineering Odaiyappa College of Engineering and Technology Theni, Tamil Nadu, India. Shiva 2476@yahoo.com 2. Professor, Madurai Institute of Engineering and Technology, Madurai, Tamilnadu, India., stanfordssk@gmail.com

# \_\_\_\_\_

#### ABSTRCT \_\_\_\_\_

# Article History:

Received 22nd May 2017 Received in revised form 29th May 2017

\_\_\_\_\_

Accepted 05.06.2017

Published on 30.06.2017

Keyword: feature extraction, matching scores, discriminating and robust. Corresponding

Author: **P** Sivakumar

Email: Shiva\_2476@yahoo.com

\_\_\_\_\_

In recent days, the security is very important in our day to day life. The human body contains various biometric traits which are well suited for the application to access control and provides security in biometric person identification technique. Identification and verification of human being by using their biometric traits are practiced now. This paper focus on a powerful methodology for Capturing, matching and verifying for human recognition with feature extraction from iris and palm print of single person. These features of an input image are compared with those of a database image to obtain matching scores. Authenticity is based on the accuracy during matching process the result is given for each person. It is desirable to develop a feature analysis method which is ideally both discriminating and robust for iris and palm print biometrics.

-----



International Journal of Research in Management, Science and Technology

whether single or multiple biometric features are used for person authentication.

# **1. INTRODUCTION**

Biometrics is the science and technology of measuring and analyzing biological data of human body, extracting a feature set from the acquired data, and comparing this set against to the template set in the database [1]. Biometric-based

techniques have emerged as the most promising option for recognizing individuals in recent years. Common practices to identify the people are by using passwords, PINs, smart cards, tokens, keys etc. but these are sometimes misplaced, forgotten, purloined or duplicate and hard to remember. However an individual's biological traits cannot be misplaced, forgotten, stolen or forged. Biometric-based technologies

include identification based on physiological characteristics (such as face, fingerprints, finger geometry, hand geometry, hand veins, palm, iris, retina, ear and voice) and behavioral traits (such as gait, signature and kevstroke dynamics) [2].Human physiological and/or behavioral characteristic can be used as a biometric trait when it satisfies the requirements like ubiquity, peculiarity, stability and collectability.

In practice, no single biometric can satisfy all the desirable characteristics mentioned above for it to be used for person authentication. This is due to the problems associated with noisy data, intra-class variation, non-universality, spoof attacks and high error rates [4].

To overcome this limitation, multiple biometric features can be used for person authentication. This resulted in the development of multimodal biometric person authentication system [4]. Thus biometric system can be classified as Uni-modal system and multimodal system based on



**Fig 1: Types of Biometrics** 

# 2. BIOMETRIC SECURITY SYSTEM

Biometric security system becomes an efficient tool compared to electronics based security systems [3]. Multimodal biometric authentication techniques attract much attention of many researches recently as the fusion between many different modalities can increase the recognition rate. The fusion can be achieved in different levels such as sensor, feature, or classification level. The literature reported that the multimodal biometric methods achieve better recognition rates than unimodal biometric methods. From the unimodal biometrics data, two traits of iris [5] and palm print [6] are recently best authentication biometrics. Biometrics authentication is known as realistic authentication is used in computer science for identificationand access control. It is also used to identify individuals in groups that are under supervision.

# **3. MULTIMODAL**

The multimodal-based authentication can help the system to increase the security and efficiency in contrast to uni-modal biometric authentication, and it would be very difficult for a rival to spoof the system because of two distinct biometrics features. Multimodal biometrics fusion techniques have attracted much attention as the supplementary



International Journal of Research in Management, Science and Technology

information between different modalities could improve the recognition performance. Information from different biometrics traits can be integrated at the feature level (integrating the features of different biometrics), score level (combining the genuine and imposter scores), or decision level (combining the decisions). Although feature sets are the rich source of information, features from these modalities may not be compatible. Moreover large dimensionality of a feature space may lead to irrelevant and the redundant information [15].



Fig 2: Examples of Multimodal

*Face Recognition*: Face recognitionhas records of different features of the face in spatial geometry form. Many kind of methods for face recognition using in different field. But, all are having objective of features measure from the face as a key factor. Face recognitionhas been used in projects to identifyundesirables in criminals and terrorists in urban areasshoplifters in stores, casinos. This kind of biometric system can easily spoofby malicious intruders and the criminals to cheat a recognitionsystem. But, Iris cannot be spoofed easily.

**Palm Print:** Palm print scanning uses is very similar to fingerprint scanning; it size is

much big, but limited factor only use in recognition system.

*Signature Verification*: It is an automated method of testing an individual's signature. This is dynamic such as direction and pressure of writing, speed and the style. Signature verification has template from 50 to 300 bytes. Disadvantages of signature verification are long-term reliability, lack of accuracy and cost.

*Fingerprint:* A fingerprint attains device, minutia extractor and minutia matcher. Commonly, this biometric recognition used in banking, military etc., but it can be spoofed easily and difficult to scan due to the causes of wearing gloves, using cleaning fluids, etc..,

# 4. IRIS DETECTION

Iris Scan: Iris gives reliable and accuracy for authentication processthan other biometric feature. Iris has different patterns in the left and right eye. So, scanning has to be done quickly for both identification and verification applications because of its large number of degrees of freedom. The amount of light entering through the pupil is controlledby diaphragm between the pupil and the sclera. Iris is composed of elastic connective tissue such as trabecular meshwork. Suitability of this as an exceptionally accurate biometric derives from:

i.The difficulty of using as an imposter person and forging.

ii. It is protection and intrinsic isolation from the external environment.

iii. Its data-rich physical structure.



Fig 3: Structure of Iris

International Journal of Research in Management, Science and Technology

iv. Its genetic properties: no two eyes are the same. The Characteristic that is dependent on genetics is the pigmentation of the iris, which determines the gross anatomy and its color that are unique to each case.

v. Its stability over time; there is no possibility of surgically modification of risk to vision and its physiological response to light, which provides a natural test against artifice. An image-processing algorithm that can encode the iris pattern into 256 bytes based on the Gabor transform.



# Fig 4: Steps of the Iris Recognition

**Graycode:**widely, Gray codes are used to facilitate errorcorrection in digital communications such as digital terrestrialtelevision.

# **Contrast Enhancement Techniques:**

- 1) Load Images
- 2) Resize Images
- 3) Enhance Grayscale Images
- 4) Enhance Color Images

Load Images: Read images

*Resize Images:*Resize the images and make the image comparison easier for same width. Preserve their aspect ratios by scaling their heights.

*Enhance GrayscaleImage:* There are three functions are suitable for contrast enhancement:

- a) imadjust,
- b) histeqand
- c) *adapthisteq*.

**Imadjust**: It is increases the contrast of the image by mapping the values of the input intensity image to new values such that, default value 1% of the data is saturated at low and high intensity of the input data.

**Histeq**:Operation of histogram equalization is enhances the contrast of images by transforming the values in an intensity image for theapproximate histogram matches of outputimage to a specified histogram.

Adapthisteq: Operation of adaptive histogram equalization is contrast-limit. It operates on small data regions rather than the entire image, unlike histeq. The contrast enhancement can be limited in order to avoid enlarge the noise which might be present in the image.

Method	Coded Pattern	Mis- identific	Security	Application
Iris Recognition	Iris pattern	1/120000 0	High	High security facilities
Finger printing	Fingerprints	1/1,000	Medium	Universal
Hand Shape Size,	Length and thickness	1/700	Low	Low- security facilities
Facial Recognition	Outline, shape and distribution of	1/100	Low	Low- security facilities
Signature	Shape of	1/100	Low	Low- security
Voice printing	Voice characteristic	1/30	Low	Telephone service

# Table1 (a): Biometric comparison List

Biometrics	Crossover Accuracy		
Retinal Scan	1:10,000,000+		
Iris Scan	1:131,000		
Fingerprints	1:500		
Hand Geometry	1:500		
Signature Dynamics	1:50		
Voice Dynamics	1:50		

Table1 (b): Biometric comparison List



# International Journal of Research in Management, Science and Technology

# 5. IRIS DETECTION AND SEGMENTATION Iris Detection:

Irises are detected even the situation of obstructions, visual noise and different levels of illumination. Eyelids and eyelashes obstructions are eliminated and Lighting reflected. Images with narrowed eyelids or eyes that are gazing away are

accepted using wavelet algorithm.

Automatic interlacing detection and correction: The result of correction in maximum quality of iris features templates from moving iris images.

*Gazing-away eyes:* A gazing-away iris image is correctly detected, segmented and transformed when we directly looking into the camera.

# Iris Segmentation:

It can achieved by following conditions:

*Perfect circles fail: It* usesVeriEye active shape models that much precisely model the contours of the eye, as perfect circles do not model iris boundaries.

The centers of the iris inner and outer boundaries are different: The iris boundary of inner and its center aremarked in red; The iris boundary of outerand its center are marked in green.

# **Locating Iris**

- 1) To locating the inner and outer boundaries of the iris
- 2) To normalize iris and
- 3) To enhance the original image

$$\max(r, x0, y0) = \left\{ \frac{\partial}{\partial r} \int_0^{2\pi} I(r * \cos\theta + x0, r * \sin\theta + y) \right\}$$

Where,

(x0, y0) denotes the potential center of the searched circular boundary, and r its radius.



Fig 5: Segmented iris



Fig 6: Normalized iris

# 6. PALMPRINT

A CCD-based scanner used to capture images in high resolution and aligns palms accurately because of its pegs for guiding the placement of hand. Digital scanners arerequires large time for scanning because of its low quality. This is reason for digital scanners cannot be used in real time applications.



Fig 7: CCD Based Scanner





Fig 8: Steps of the palmprint Recognition System

# Preprocessing

Preprocessing is used to correct distortions, align different palmprints, and to crop the region of interest for feature extraction. Preprocessing commonly focuses on five steps

1. Binarizing the palm images

- 2. Boundary tracking
- 3. Identification of key points
- 4. Establishing a coordination system and
- 5. Extracting the central part.

The third step can be well equipped by two approaches: *tangent* based and *finger* based. The tangent based approach is preferred. This approach considers the edges of the two finger holes on the binary image to be traced. The common tangent of the two finger holes is considered to be the axis. The key points for the coordination system are calculated as the midpoint of the two tangent points.

The palmprint recognition system includes preprocessing followed by ROI extraction. After ROI extraction, features are extracted using the feature extraction algorithms.

Print ISSN: 2249 - 3492, Online ISSN: 2249 - 3506

International Journal of Research in Management, Science and Technology



Fig 9:(a)key points and coordinate system(b)ROI extraction

# **ROI** extraction

It considers middle area of palm segmentation after the image for preprocessing. For feature extraction different algorithms are segment as circular, half elliptical or square regions. The square region is widely used. The cropped image is then passed through an ordinal filter, which blurs the image. In this blurred image, the minor lines smothered. Infeature extraction the major lines are affected, but they are distinct.

# **Ordinal Filters**

The ordinal features are extracted by passing the input images through the ordinal filters. For the registration experiments all the operations are performed in three dimensions. We just show concepts in 2D cases for better illustration. Easily, it can be extended to 3D. Comparison of neighboring regions Gabor filter is a well-known differential filter. It has disadvantages of the span of the Gabor filter is limited by the size of its sub-fields, therefore it is difficult to capture useful information from small regions across large distances.

With multiple lobes the ordinal filter can extended more complex microstructures than the dipole filter. Also, using different shapes of individual lobe, the ordinal filter



Print ISSN: 2249 - 3492, Online ISSN: 2249 - 3506

International Journal of Research in Management, Science and Technology

can be planned to extract different specified micro-structures from the images.



Fig 10:(a)A 3<sup>rd</sup> Order Ordinal Filter Applied (b)A 4<sup>th</sup> Order Ordinal Filter Applied



Fig 11: Sample of ordinal filter used

# Fusion:

Fusion of multiple features of an individual can improve the matching accuracy of a biometric recognition system. a system that consolidates multiple sources of biometric information that avoid noisy data, intra-class variations, spoof attacks and unacceptable error rates of a unibiometricrecognition system. Multimodal biometric systems are capability of utilizing, more than one physiological or behavioral characteristic for enrollment, verification, or identification. The multimodal biometric is very promising applications and theoretical challenges in recent years.



Fig 12: Accuracy plots of individual recognizers



ig 13: Accuracy graph for combined classifier





Fig 14: curve for palmpint, iris and fusion

# 7. PATTERN MATCHING

To obtained vector in a binary pattern matching is very important to represent code. It is easier to find the difference between two binary code-words than between two number vectors. If the feature vector has to code first observed some of its characteristics from it. Now found that all the vectors that we obtained have a maximum value that is >0 and a minimum value that is < 0. If "Coef" is the feature vector of an image than the following measuring scheme converts it to its Equivalent code word

- ★ if Coef(i) >= 0 then Coef(i)=1
- ★ if Coef(i) < 0 then Coef(i)=0

# 8. IDENTIFICATION AND VERIFICATION

Every security system has goals of two: *Identification* and *verification*itbased on the needs of the environment. In the *verification*: In this the system checks if the user data that was entered is correct or not (e.g., username and password). It is a one-to-one search.

*Identification*: In this the system tries to discover who the subject is without any input information. It is a one-to-many comparison.

#### 9. RELATED WORK

# A. Existing system

A multimodal biometric system that alleviates the limitations of the uni-modal

Print ISSN: 2249 - 3492, Online ISSN: 2249 - 3506

International Journal of Research in Management, Science and Technology

biometric systems by fusing the information from the respective biometric sources was general developed. А approach was explained for the fusion at score level by combining the scores from multiple biometrics using triangular norms (t-norms) due to Hamacher, Yager, Frank, Schweizer and Sklar, and Einstein product. This study aims at tapping the potential of t-norms for multimodal biometrics. The approach renders very good performance as it was quite computationally fast and outperforms the score level fusion using the combination approach (min. mean. and sum) and classification approaches like SVM, logistic linear regression. MLP. etc. The experimental evaluation on three databases confirms the effectiveness of score level fusion using t-norms.

In this phase, the two set features will be extracted from iris and palm images. At first, the palm image will be preprocessed to get the palm ROI (Region of interest), and palm print features of wrinkles, ridges and principal lines will be extracted from the palm ROI. On other hand, localization process will be applied on the iris images; some useful features will be extracted. Subsequently, the extracted features will be fused together at the feature level to construct the multi-biometric template.

# **B.** Proposed System

In this phase, some additional features will be selected based on iris and knuckle print of image presented in the database. The additional features provided based on iris and knuckle print image will provide the significant improvement as compared with existing algorithm. The implementation will be done in MATLAB and the performance of the algorithms will be analyzed using false alarm rate (FAR), False rejection rate (FRR) and accuracy. This result will be send to mobile through message.

# **10. MODULE DESCRIPTION**

The following three modules are in this project.

a. Iris detection:



International Journal of Research in Management, Science and Technology

In eye information is carryingby iris part only. It lies between the sclera and the pupil. The next step is segmenting the iris part from the eye image. Using the eigen values inner and outer boundaries of iris are located by finding the edge image. This mathematical pattern-recognition techniques is used in irises of an individual's eyes, whose complex random patterns are stable, unique and can be seen from some distance.

# **b. Palm Pre-Processing:**

To understand palmprintrecognition concept, one must first understand the valleys of a palm and physiology of the ridges. When recorded, a palm print appears as a series of dark lines and represents the high, peaking portion of the friction ridged skin while the valley between these ridges appears as a white space and shallow portion of the friction ridged skin. palm features exploits by Palm recognition technology. A palm recognition system is planned to interpret the flow of the overall ridges to assign a classification and then after extract the minutiae detail a subset of the total amount of information available, desire information to effectively search a large treasury of palm prints. Minutiae are limited based on location, direction, and orientation of the ridge endings along a ridge path.

# C. PCA Fusion & Recognition

Principal Component Analysis algorithm builds a fused feature of input palm prints and Iris as a weighted of all features. The classifier based on the Euclidean distance has been used which is obtained by calculating the distance between the image which are to be tested and the already available images used as the training images. Then the minimum distance is observed from the set of values.

# **11. CONCLUSION**

A proposed work is to enlarge the algorithm forPowerful recognition with human iris and palmprint pattern identification. It done byincreasing FRR more than 0.33% as the VeriEyealgorithm results with FRR 0.32% and FAR 0.001% for other applications. Ordinal feature extraction for robust and fast matching use in healthcare application, suitable for reliable, fast and secure person identification. Proposed algorithm focus on the accurate of iris and palmprintidentification even if the images are occlude and it will also focus on robust iris and palmprintrecognition with narrowed eye which solves all the security related problems in system.

# **12.REFERENCES**

[1] MadhaviGudavalli, S.ViswanadhaRaju, A. VinayaBabu and D.Srinivasa Kumar, "Multimodal Biometrics - Sources, Architecture & Fusion Techniques: An Overview", In proc. of IEEE International Symposium on Biometrics and Security Technologies, pp. 27-34, 2012.

[2] Muhammad Khurram Khan and Jiashu Zhang, "Multimodal face and fingerprint biometrics authentication on space-limited tokens", Neuro Computing, Vol. 17, No. 12, pp. 3026 – 3031, 2008.

[3] L.Gorman, "Comparing passwords, tokens and biometrics for user authentication," IEEE Proc., vol. 91, no.12, Dec. 2003.

[4] A.K. Jain, A Ross and S. Prabhaker, "An introduction to biometric recognition," IEEE Trans. Circuits and Systems for Video Technology, vol. 14, no. 1, pp, 4-20, Jan. 2004.

[5] Aly I. Desoky, Hesham A. Ali and Nahla B. Abdel-Hamid, "Enhancing iris recognition system performance using templates fusion", Ain Shams Engineering Journal, vol.3,pp. 133–140, 2012.

[6] S.S. Kulkarni and R.D.Rout, "Secure Biometrics: Finger Knuckle Print", International Journal of Advanced Research in Computer and Communication Engineering, Vol. 1, no. 10, 2012.

[7] V. U. Kale, R. A.Wakode and Rinky L. Batra3, "Finger Knuckle System for Human Identification: A Literature Survey ",InternationalJournal of Emerging Technology and Advanced Engineering, Volume 5, Issue 1, January 2015).

[8] R. Szewczyk, K. Grabowski,M. Napieralska, W. Sankowski, M. Zubert, A. Napieralski, "A reliable iris recognition algorithm based on reverse biorthogonal

International Journal of Research in Management, Science and Technology



wavelet transform", Pattern RecognitionLetters, vol. 33, no. 8, pp. 1019– 1026,2012.

[9] Acır, N., Özdamar, Ö. Güzeliş, C., "Automatic classification of auditory brainstem responses using SVM-based feature selection algorithm for threshold detection," Engineering Applications of Artificial Intelligence, Vol.19, 209-218, 2006.

[10] Valentini, G., Muselli, M., Ruffino, F.,"Cancer recognition with bagged ensembles of support vector machines," Neuro computing, Vol. 56, 461-466, 2004.

[11] Zhang, Y.L., Guo, N., Du, H., Li, W.H., "Automated defect recognition of C- SAM images in IC packaging using Support Vector Machines," The International Journal of Advanced Manufacturing Technology 25, 1191-1196,2005.

[12] Karabatak, M., Ince, M.C., "An expert system for detection of breast cancer based on association rules and neural network," Expert Systems with Applications, Vol.36, pp.3465-3469, 2009.

[13] Mehmet Fatih, A., "Support vector machines combined with feature selection for breast cancer diagnosis," Expert Systems with Applications, Vol. 36, pp.3240-3247,2009.

[14]P. S. Sanjekar and J. B. Patil, "An overview of multimodal biometrics", Signal & Image Processing an International Journal (SIPIJ) Vol.4, No.1, February 2013.

[15] Wang, Y., Tan, T., Jain, A. K., "Combining face and iris biometrics for identity verification",In: Proc. of Fourth International Conference on Audio- and VideoBased Biometric Person Authentication (AVBPA). Guildford, UK, pp. 805–813, 2003.

[16] Verlinde, P., Cholet, G., "Comparing decision fusion paradigms using K-NN based classifiers, decision trees and logistic regression in a multi-modal identity verification application", In: Proc. of Second International Conference on Audioand Video-Based Biometric Person Authentication (AVBPA). Washington, DC, USA, pp. 188–193, 1999. [17] Chatzis, V., Bors, A.G., Pitas, I., "Multimodal decision-level fusion for person Authentication", IEEE Trans. Systems Man Cybern. Part A: Systems Humans, vol 29, no.6, pp.674–681, 1999.

[18] Fahmy, M.S., Atyia, A.F., Elfouly, R.S., 2008. Biometric fusion using enhanced SVM classification. In: 2008-Fourth International Conference on Intelligent Information Hiding And Multimedia Signal Processing. Harbin, pp. 1043–1048.

[19] Park, H.A., Park, K.R., "Iris recognition based on score level fusion by using SVM", Pattern Recognition Letter, vol. 28, no.15, pp. 2019–2028, 2007.

[20]MadasuHanmandlu,Jyotsana Grover, AnkitGureja and H.M. Gupta, "Score level fusion of multimodal biometrics using triangular norms", Pattern Recognition Letters, vol. 32, pp.1843–1850,2011

[21] Swathi S. Dhage, SushmaShridharHegde, K. Manikantan and S. Ramachandran, "DWT-based Feature Extraction and Radon Transform Based Contrast Enhancement for Improved Iris Recognition", Procedia Computer Science, vol.45, pp.256-265, 2015.

[22] Lan LIN, Ge ZHAO, Yan-Dong TANG, Jian-Dong TIAN and Si-Yuan HE, "Illumination Compensation for Face Recognition Using Only One Image", ActaAutomaticaSinica, vol. 39, no. 12, pp. 2090-2099, 2013.

[23] Patricia Melin, Daniela Sanchez and Oscar Castillo, "Genetic optimization of modular neural networks with fuzzy response integration for human recognition"

Information Sciences, pp.1-19, vol.197, 2012

[24] Shoichiro Aoyama, Koichi Ito and Takafumi Aoki, "A finger-knuckle-print recognition algorithm using phase-based local block matching", Information Sciences, vol.268, pp. 53-64, 2014.

[25] JialiangPeng, Ahmed A. Abd El-Latif, Qiong Li and XiamuNiu, "Multimodal biometric authentication based on score level fusion of finger biometrics", International Journal for Light and Electron Optics, vol. 125, no. 23, pp. 6891-6897, 2014.



International Journal of Research in Management, Science and Technology

[26] Muhammad Khurram Khan and Jiashu Zhang, "Multimodal face and fingerprint biometrics authentication on space-limited tokens", Neurocomputing, vol. 71, pp. 3026-3031, August 2008.

[27] T. Zhang, X. Li, D. Tao, and J. Yang, "Multi-modal biometrics using geometry preserving projections", Pattern Recognition, vol. 41, no. 3, pp. 805-813, 2008.